Analisi Numerica: Metodi e Software Matematico

Progetto cofinanziato dal MURST - 1998–2000

A Random Generator for Large–Scale Linearly Constrained Quadratic Programming Test Problems

C. Durazzi V. Ruggiero

Dipartimento di Matematica
Università di Ferrara

L. Zanni

Dipartimento di Matematica
Università di Modena e Reggio Emilia

Monografia n. 6

Ferrara 2000

Monografie del Programma di Ricerca Scientifica 1998–2000
“Analisi Numerica: Metodi e Software Matematico”
cofinanziato dal Ministero per l’Università e
la Ricerca Scientifica e Tecnologica nell’anno 1997.

Monographs of the 1998–2000 Scientific Research Program
“Numerical Analysis: Methods and Mathematical Software”
supported in 1997 by the Italian Ministry for the University
and the Scientific and Technological Research.

http://www.unife.it/AnNum97

Abstract

In this paper we describe a random generator for large and sparse quadratic programming problems that frequently arise in different areas of applied science. This generator is an useful tool in testing algorithms on QP problems with different features, since it allows us to vary many parameters which characterize the problems.
The procedure used to generate a QP problem as well as some details for its implementation are explained.
Finally, we report an analysis of the numerical results, obtained by the routine E04NFK of the NAG library on the test problems produced by the generator.

C. Durazzi V. Ruggiero
Dipartimento di Matematica, Università di Ferrara, Via Machiavelli 35, Ferrara, Italy.
E-mail: {dzc,rgv}@dns.unife.it.

L. Zanni
Dipartimento di Matematica, Università di Modena e Reggio Emilia, Via Campi 213/b, 41100 Modena, Italy. E-mail: zanniluca@unimo.it.

Contents

CHAPTER 1

Introduction

In many areas of science and technology it is required to solve the following linearly constrained quadratic programming (QP) problem

$$\begin{array}{ll} \textit{minimize} & f(x) = \frac{1}{2}x^T Gx + q^T x \\ \textit{subject to} & Cx = d, \qquad Ax \geq b, \end{array} \tag{1.1}$$

where G is a symmetric matrix of order n, C is an $m_e \times n$ matrix of full row rank ($m_e \leq n$) and A is an $m_i \times n$ matrix.
At the moment, attention is greatly focused on large QP problems where G, C and A may be sparse matrices, without a particular structure. These large problems are basic to many applications of data analysis, such as image restoration [1], pattern recognition based upon support vector machine technique [3] and constrained bivariate interpolation [5]. Furthermore, large QP problems arise as subproblems of the class of symmetric cost approximation methods [13] for large–scale nonlinear programming or variational inequality problems when the auxiliary function is a convex quadratic function or the gradient map of a convex quadratic function. See, for example, the sequential quadratic programming method or, for the variational inequalities, the linear approximation methods [12] and the descent methods based upon projective gap functions [14].
In order to make clear the "effectiveness" of the solvers proposed in literature for large QP problems, it is necessary to evaluate the numerical behaviour of these methods by an extensive experimentation on vaste sets of test problems with different features.
Well–known collections of QP problems of the form (1.1) are contained in CUTE [2] (http://www.cse.clrc.ac.uk/Activity/CUTE) and in the repository at the URL http://www.doc.ic.ac.uk/∼im/#DATA [9] (see also the following URL for a list of testcases in optimization: http://plato.la.asu.edu/topics/testcases.html).
The aim of this work is to describe a generator for random, large and sparse quadratic programs. This generator enables us to prefix the most part of the parameters that characterize a problem and, above all, it permits to specify the distribution of the singular values of the matrices of the constraints and the spectrum of the hessian and the reduced hessian of the objective function. Thus we can generate poorly or well–conditioned problems of arbitrary size, number of constraints and level of sparsity. Varying in a convenient way the parameters which the test problems depend on, we can reflect the features of the quadratic programs arising in many practical applications.
In Chapter 2, we describe the technique for randomly generating QP problems with assigned features. In Chapter 3, we report the way of storing the sparse matrices of the QP problem and some details of the implementation of the generator. In Chapter 4, we consider a set of test problems produced by this generator and we show some numerical

results obtained by solving the test problems with the routine E04NKF of the NAG library [11].

Chapter 2

A procedure for randomly generating a QP problem

We assume that the following data are given:

- the sparsity of the $n \times n$ matrix G ($spars(G)$) and of the $m \times n$ matrix B ($spars(B)$), where $B = \begin{pmatrix} C \\ A \end{pmatrix}$ denotes the constraint matrix ($m = m_i + m_e$); furthermore we set $f = \begin{pmatrix} d \\ b \end{pmatrix}$;

- the rank $r(G)$, the spectral condition number $K(G)$ and the maximum and the minimum nonzero eigenvalues, denoted by $\phi_{max}(G)$ and $\phi_{min}(G)$, of the Hessian matrix G of (1.1); for convex QP problems, the maximum eigenvalue of G is obtained by $\phi_{max}(G) = K(G)\phi_{min}(G)$;

- the spectral condition number $K(B)$ and the minimum nonzero singular value $\sigma_{min}(B)$ of the matrix B; the rank of B is chosen equal to $min(m, n)$ and the maximum singular value of B is $\sigma_{max}(B) = K(B)\sigma_{min}(B)$;

- a solution x^* of (1.1), with entries x_i randomly generated from an uniform distribution in $(-1, 1)$;

- the number m_a of the inequality constraints that are active in x^*; we denote by nac the value $m_a + m_e$, so that $nac \geq m_e$;

- an m-vector $\begin{pmatrix} \mu^* \\ \lambda^* \end{pmatrix}$ of the multipliers associated to x^*, with null elements for the entries corresponding to the inactive inequality constraints in x^*, $\mu_i^* = 10^{-z_i \cdot ndeg}$ for the indices corresponding to the equality constraints and $\lambda_i^* = 10^{-z_i \cdot ndeg}$ for the indices corresponding to the active inequality constraints; here z_i is randomly generated in $(0, 1)$ and $ndeg$ is an integer parameter which specifies the level of degeneracy;

- the rank $r(Z^T G Z)$ and the spectral condition number $K(Z^T G Z)$ of the reduced Hessian $Z^T G Z$, where Z is chosen as an orthogonal basis of the null space of the matrix given by the equality constraints and the inequality constraints active in x^*.

The matrix G of (1.1) is generated by its spectral decomposition

$$G = VDV^T = V \begin{pmatrix} D_1 & 0 \\ 0 & D_2 \end{pmatrix} V^T \tag{2.1}$$

where D is a diagonal matrix with maximum and minimum nonzero eigenvalues $\phi_{max}(G)$ and $\phi_{min}(G)$ respectively, and $r(G)-2$ diagonal entries randomly generated in ($\phi_{min}(G)$, $\phi_{max}(G)$); in particular, the diagonal submatrix D_2 of order $n-nac$ has $r(Z^TGZ)$ positive diagonal entries chosen so that the condition number of D_2 is $K(Z^TGZ)$.
The matrix V is an orthogonal matrix obtained as product of a number of random Givens rotations R_{ij} such that the matrix G is filled until the prefixed level of sparsity is attained. A random Givens rotation R_{ij} is obtained by randomly generating two different positive integers i and j in the interval $[1, n]$. Then we randomly generate a real number α in the interval $[-1, 1]$ and we set $\alpha = r_{j,j} = r_{i,i} = \cos(\theta)$; consequently, $r_{i,j} = -r_{j,i} = \sqrt{1 - r_{i,i}^2}$.
Now, we partition the matrix V in $\begin{pmatrix} V_1 & V_2 \end{pmatrix}$, where V_1 and V_2 represent the first nac and the last $n - nac$ columns of V respectively.
In order to generate the matrix of constraints B, we construct the $m \times n$ matrix $\begin{pmatrix} \tilde{B} \\ \bar{B} \end{pmatrix}$, where $\tilde{B}$ is the $nac \times n$ matrix of the equality constraints and the active inequality constraints in x^*, and $\bar{B}$ is the $(m - nac) \times n$ matrix composed by the remaining rows of B. We write $\begin{pmatrix} \tilde{B} \\ \bar{B} \end{pmatrix}$ as follows:

$$B = \begin{pmatrix} \tilde{B} \\ \bar{B} \end{pmatrix} = \begin{pmatrix} U_1 & 0 \\ 0 & U_2 \end{pmatrix} \begin{pmatrix} S_1 & 0 \\ 0 & S_2 \end{pmatrix} \begin{pmatrix} V_1^T \\ V_2^T \end{pmatrix} = \begin{pmatrix} U_1 S_1 V_1^T \\ U_2 S_2 V_2^T \end{pmatrix} \tag{2.2}$$

where S_1 is a diagonal matrix of order nac with prefixed condition number $K(B)$ and nac positive diagonal entries included in $[\sigma_{min}(B), \sigma_{max}(B)]$; S_2 is an $(m - nac) \times (n - nac)$ matrix with $min(m, n) - nac$ positive diagonal entries randomly generated and such that the condition number of $\begin{pmatrix} \tilde{B} \\ \bar{B} \end{pmatrix}$ is still $K(B)$. The rank of $\begin{pmatrix} \tilde{B} \\ \bar{B} \end{pmatrix}$ is $min(m, n)$.
The matrices U_1 and U_2 are orthogonal matrices of order nac and $m - nac$ respectively, generated as product of random Givens rotations, so that we achieve the prefixed level of sparsity for B in the matrix $\begin{pmatrix} \tilde{B} \\ \bar{B} \end{pmatrix}$.
From (2.2) we deduce that V_2 represents an orthonormal basis for the null space of $\tilde{B}$:

$$\tilde{B}V_2 = U_1 S_1 V_1^T V_2 = 0$$

Thus, if we put $Z = V_2$, from the following relation

$$V_2^T G V_2 = V_2^T \begin{pmatrix} V_1 & V_2 \end{pmatrix} \begin{pmatrix} D_1 & 0 \\ 0 & D_2 \end{pmatrix} \begin{pmatrix} V_1^T \\ V_2^T \end{pmatrix}$$

$$= V_2^T (V_1 D_1 V_1^T + V_2 D_2 V_2^T) V_2 = D_2$$

we have that the reduced Hessian has rank $r(Z^TGZ)$ and condition number $K(Z^TGZ)$, as prefixed.
Then, we put

$$f = \begin{pmatrix} \tilde{B} \\ \bar{B} \end{pmatrix} x^* - \begin{pmatrix} 0 \\ \epsilon \end{pmatrix}$$

where ϵ is a vector with positive random elements.
Finally, we obtain the n-vector q of the objective function in (1.1) from the Kuhn Tucker conditions:

$$q = -Gx^* + A^T \lambda^* + C^T \mu^*.$$

Chapter 3

Implementation of the test problem generator

A random test problem generator for large–scale sparse linearly constrained convex QP problems, based on the technique described in the previous Chapter, is written in Fortran 77.
The source program, contained in the file **test98.f**, is available at the following URL: http://www.unife.it/AnNum97/index2.htm.
An exhaustive documentation, about the input data that the user has to supply and about the output files produced by the program, is reported in the comments of the source file. At the same URL, it is possible to get a file containing an example of the input data (**inputtest98**) and a file showing the messages produced by the program (**outputtest98**).
In the following, we explain some details of the implementation of the test problem generator.
The nonzero eigenvalues of G and the nonzero singular values of B can be randomly generated in a convenient interval, according to a log–uniform distribution or an uniform distribution or they can be equally spaced between the extrema of the interval in question. If the input variable *indg* (or *indb* for the matrix B) is equal to 0, a log–uniform distribution for randomly generating the eigenvalues of G (or the singular values of B) is used; if $indg = 1$ ($indb = 1$, respectively) an uniform distribution is used; otherwise, the eigenvalues of G (or the singular values of B) are equally spaced between the smallest and the largest eigenvalues (or singular values). For the matrices G and B, the user has to supply $condg = \log_{10}(K(G))$, $condb = \log_{10}(K(B))$, $condzgz = \log_{10}(Z^TGZ)$ ($\leq condg$) and $condba = \log_{10}(\tilde{B})$ ($\leq condb$). Furthermore, the following data have to be introduced:

- for the matrix G, the minimum positive eigenvalue *glmin* and the rank *ngrango* (G is a positive semidefinite matrix); the maximum eigenvalue of G is $10^{condg} \cdot glmin$;
- for the matrix Z^TGZ, the minimum positive eigenvalue *zgzlmin* ($\geq glmin$) and the rank *nzgzrango* ($\leq ngrango - nac$); the maximum eigenvalue of Z^TGZ is $10^{condzgz} \cdot zgzlmin$;
- the minimum nonzero singular value *blmin* of the matrix B; the rank of B is $\min(m, n)$;
- the minimum nonzero singular value *balmin* ($\geq blmin$) of the matrix $\tilde{B}$; the rank of $\tilde{B}$ is *nac*.